

E100

Getac

Getac E100 Fully Rugged Tablet

- 800 NITs sunlight readable display with touchscreen
- Light weight 3 lbs. design
- MIL-STD 810G and IP65 compliant
- 80GB solid state drive
- Full magnesium alloy case
- Fan-less design
- Industry's-best 5 year bumper-to-bumper warranty



The Getac E100 Fully Rugged Tablet

The E100 is one of the lightest fully rugged tablet PC on the market weighing in at a mere 3 lbs. Despite its trim look and feel, the E100 is every bit as tough as the heavyweights. It meets all MIL-STD 810G and IP65 standards and can be configured for -20°C cold weather operation.

The E100 comes standard with many upgraded features including a large 8.4 inch super-bright 800 NIT sunlight readable display with touchscreen for amazing viewability even in direct sunlight. The E100 also includes Bluetooth, integrated GPS and WLAN. For added connectivity, GPS and 3G Gobi™ 2000 are available.

The Getac E100 Fully Rugged Tablet comes standard with an 80GB solid state drive. The E100 comes with Windows® 7 operating system and has both a numeric keypad and programmable quick keys. The Getac E100 is covered by the industry's-best 5 year bumper-to-bumper warranty.

The E100, with its rugged design and powerful software tools, is built to handle the task wherever your job takes you.

Getac E100

Specifications

ruggedsales@getac.com
www.getac.com
949.681.2900

Getac, Inc.
43 Tesla
Irvine, CA 92618

Ruggedness	Fully Rugged MIL-STD 810G and IP65 compliant
Operating System	Genuine Windows 7 Professional
CPU	Intel® N450 1.66GHz 667MHz FSB 512KB L2 cache
Memory	2GB
Storage	SATA 80GB solid state drive*
VGA Controller	Intel® Media Accelerator 3150
Display	8.4" SVGA (800 x 600) TFT 800 NITS sunlight readable LED display with glove-friendly multi-touch technology
Keyboard	Numeric and quick keys with backlight keypad
Webcam	Intergrated 2.0MP camera - option
Expansion Slot	PCMCIA Type II + smart card reader
Security	TPM 1.2 Cable lock lock

Communications	10/100/1000 base-T Ethernet WLAN 802.11 a/g/n Bluetooth (v2.1+EDR class 2) GPS (with internal antenna and pass through) - option 3G - Gobi™ 2000 - option
Power	AC adapter (50W, 100-240V, 50/60Hz) Li-Ion smart battery (5200mAh) Hot-swappable battery - option (occupies PCMCIA slot)
Dimensions and Weight	11" x 7.24" x 1.26" (280 x 184 x 32 mm) 3 lbs (1.4 kg)**
Temperature	Operating temp: -4°F to 140°F (-20°C to 60°C) (Low temp: -4° to -20°) Storage temp: -40°F to 167°F (-40°C to 75°C) Humidity: 5% to 95% RH, non-condensing
I/O Interfaces	DC in x 1 USB 2.0 x 2 Docking port x 1 Network (RJ-45) x 1 Serial port (RS-232) x 1 Audio Output x 1 Built-in microphone x 1 RF antenna pass through (for GPS/WWAN) x 1
Warranty	5 Year bumper-to-bumper warranty standard†

Specification subject to change without notice.

Battery performance will vary based on software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. As with all batteries, maximum capacity decreases with time and use and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

* For storage and solid state drives, 1GB = 1 billion bytes; actual formatted capacity less.

** Weight varies by configuration and manufacturing process.

† Industry's best 5 year bumper-to-bumper limited warranty standard. For warranty terms and conditions visit www.getac.com

Copyright 2012, Getac, All Rights Reserved. Getac and the Getac logo are either registered trademarks or trademarks of Getac Technology Corporation in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and in other countries. All other trademarks are the property of their respective owners.